

ADLER Legno-Holzbodenseife

7031000210

Treating concentrate for oil-treated wooden floors and parquet in the interior for DIY and professional use

	PRODUCT DESCRIPTI	ON
General	Premium soap for regular cleaning and maintenance. The floor is cleaned, maintained and refined in one step. High cleaning power with a neutral pH-value. ADLER Legno-Holzbodenseife leaves a silk-matt protecting film. Antistatic.	
Application areas	Wooden floors and parquet treated with oil, wax and leach, as well as cork and laminate.	
	PROCESSING	
Instructions for use	 Please shake the product before use. Do not apply if temperatures are below 5 °C or higher than 30 °C and/or relative humidity > 80%. Apply uniformly, but not too wet, with a mop or cloth. Do not wipe with water afterwards, as the protective film will be removed. Warning: In spite of the neutral pH-value (carry out preliminary tests) slight discolorations can occur, in case of wood rich in extractives, such as Oak. 	
Application technique	Application method Dilution (thinning) Mixing ratio water	Wiping Water Oiled floors: 1:100 Laminate: 1:300
	Quantity to be added	Oiled floors: approx. 8 – 10 ml

The shape, the properties and moisture of the substrate affect the consumption/yield.

Laminate: approx. 2.5 - 3 ml

approx. 500

01-17 ZKL 7031

p.t.o.

ADLER-Werk Lackfabrik, A-6130 Schwaz Tel: 0043/5242/6922-301, Fax: 0043/5242/6922-309, Mail: technical-support@adler-lacke.com

Our instructions for use are based on knowledge available currently and shall guide the purchaser / user to the best of one's knowledge, but, however, must be clarified for the areas of application and processing conditions on a case-to-case basis. The purchaser / user decides about the acceptance and use of the delivered product at his / her own risk, which is why we recommend that a sample piece be prepared to check the acceptability of the product. Our general terms and conditions of sale are otherwise applicable. All previous data sheets are rendered invalid with the issue of this one. Rights reserved for modification of the container sizes, colour shades and degree of gloss.

Product (ml) to water (l)

Yield per application (m²/l)

Drying times (at 23 °C and 50 % rel. humidity)	Drying approx. 1 – 2 hours	
	The figures given above are reference values. The drying time depends on the type of substrate, coat thickness, temperature, ai exchange and relative atmospheric humidity.	
	Lower temperatures and/or high level of atmospheric humidity can increase the drying time.	
	SUBSTRATE	
Type of substrate	Wooden floors and parquet treated with oil, was and leach, as we as cork and laminate.	
Preparation of the substrate	Dry cleaning with a broom or hoover.	
	PRODUCT APPLICATION	
Application of the product	1-3 x ADLER Legno-Holzbodenseife Natural 7031000210	
	ORDERING INFORMATION	
Size of trading unit	1 I and 2.5 I	
Colour / degree of gloss	ADLER Legno-Holzbodenseife Natural 7031000210	
	FURTHER DETAILS	
Durability / storage	At least 3 years in the original sealed containers.	
	Make sure the product is protected against moisture, direct sunlight, frost and high temperatures (above 30 °C).	
GISCODE	GU 40	
Safety-related information	Please pay attention to the associated safety data sheet. The conversion can be accessed on the Internet at www.adler-lacke.com	